

Cross-walking Three-Axis/Five-Axis Servo Driven Robots

MEWE-80/MEWE-80s





## 注塑用机械手 TAKE-OUT ROBOT

ME WE - 80 ME WE - 80s



## STANDARD FUNCTION

256
Packaging motion Max. 256 points

115 × 2

Free packaging motion 115points × 2stage

Forward and rotate at removing side

Posture control during traverse

Posture midway descent at release side

E jector link

Defective product reject circuit

Initial defective product reject circuit

Delayed arm descent

Midway runner release Move Revert

Runner release within mole

Additional vacuum sensing unit 2 circui

Delayed traverse

Undercut extract circuit

Start signal of conveyor

100 Internal memory for Max 100 molds

Lock function of setting value

Extraction from fixed mold

2

Two language exchange - ChineseÆnglish





- 岳尺寸C是1400mm时,尺寸B为1920mm
- v/hen dimension C is 1400mm , B is 1920mm
- 当尺寸C是1600mm时,尺寸B为2100mm!
- when dimension C is 1600mm, B is 2100mm

www.topstarltd.com

eature and scope of the product does not guarantee the product attributes, only for reference. Our scope of delivery and services provided are based solely on the terms of delivery and services provided are based solely on the terms of the contract Lechnical data and illustration are only for reference. We reserve the rights of changing.

TSD-2021-12

GUANGDONG TOPSTAR TECHNOLOGY CO.,LTD

∠ ADD - No.2 Chuangxin Road, Datanglang, Dalingshan Town, Dongguan Cit Suangriang Province

