



A	Overall height	2190mm - 2220mm	Air ripper in chuck circuit
B	Overall length	2250mm	WT
C	Travel stroke	1800 mm	WT gate cutting on crossmember or moving
D	Main-arm vertical stroke	1200 mm	4
E	Main-arm vertical standby	230 mm	Additional vacuum sensing unit - 4 circuits
F	Robot crosswise in chuck mount position	325 mm	4
G	Base side face - Box end	405 mm	Product gripping 4 circuits
H	Sub-arm vertical standby	280 mm	Mold close during ascend
I	Main-arm reach max	1200 mm	Relia flex unit
J	Main-arm crosswise stroke max	935 mm - 700 mm	Ejector return link
K	Main-arm crosswise standby min	265 mm - 900 mm	12
L	Main/sub-arm proximity min	260 mm	EUROMAP 12
M	Sub-arm crosswise stroke max	700 mm	67
N	Sub-arm crosswise standby min	250 mm	EUROMAP 67
O	Crosswise arm end - Box end	1740 mm	

Feature and scope of the product does not guarantee the product attributes only for reference. Our scope of delivery and services provided are based solely on the terms of delivery and services provided are based solely on the terms of the contract. Technical data and illustration are only for reference. We reserve the rights of changing.

TSD-2021-12

GUANGDONG TOPSTAR TECHNOLOGY CO., LTD.

2

ADD: No.2 Chuangxin Road, Dahefang, Dalingshan Town, Dongguan City,
Guangdong Province.

TEL: 0769-8305 0999 FAX: 0769-8584 5562

Domestic Service Hotline: 400-096-8005

